

Thermocenter.

TC40/TC100

The SalvisLab Thermocenter sets standards in quality and design. Short heating and precise temperature control make the Thermocenters true experts in heating and drying tasks. The peculiarity of this multi-functional dry and heat cabinet is in a unique system «everything-in-the-door». Above all, the system guarantees full flexibility in the placement of the interior. Thanks to the touch screen, the operation is even easier and more manageable than before. SwissTEQ in its unique form.



Technical specifications

External dimensions (wxhxd) in mm
Internal dimensions (wxhxd) in mm
Internal volume (l)
Shelves (standard/max.)
Temp. range approx. $>5^{\circ}\text{C}$ oRt to $(^{\circ}\text{C})$
Temp. variation at $50/150^{\circ}\text{C}$ ($\pm^{\circ}\text{C}$)
Temp. fluctuation at 100°C ($\pm^{\circ}\text{C}$)
Heating-up time $70/150^{\circ}\text{C}$ (in min.)
Power (w)
SalvisTEQ controller
Display
Ports

TC40

460x490x526
340x370x330
40
1/8
200
0.4/1.5
0.1
10/24
1100
Yes
Touch
USB, RJ45

TC100

570x620x656
450x500x460
100
1/8
200
0.4/1.7
0.1
15/35
1100
Yes
Touch
USB, RJ45

Options

Product temperature controller
Program- and user package
Process graph
Redundant PT-100 probe
Factory temperature mapping
LAN-Interface
Additional memory
Entry port 20 mm
Entry port 40 mm
IQ/OQ draft paper, 3 hard copiest
+ point calibration

Accessories

Stainless steel shelves (standard)
Perforated stainless steel shelves
Wire shelves
Exhaust air adapter
Fresh air filter
Product temperature probe
Stacking adapter
Wall bracket